

	POWER LEVEL	DISPLACEMENT (CUBIC CM)	BORE (mm)	STROKE (mm)	WEIGHT (kg)	OIL CAPACITY (Liters)	VALVE		CYLINDER		AIR CLEANER			IGNITION	LUBRICATION		
							SIDE VALVE	OHV	ALUMINUM	CAST IRON SLEEVE	OILED FOAM	PAPER	DUAL-CLEAN	MAGNETRON	SPLASH TUBE	PRESSURE FILTRATION	PRESSURE LUBRICATION
<b>HAND HELD</b>																	
Ecotek	0.75	34	40.1	27.18	3.53	0.08	*		1		*				*		
<b>WALK-BEHIND</b>																	
Classic	35	148	65.1	44.4	8.96	0.6	*		1		*			*	*		
Sprint	375	148	65.1	44.4	8.96	0.6	*		1		*			*	*		
Sprint/Quattro	40	158	65.1	47.5	9.98	0.6	*		1		*			*	*		
ES	40	190	68.3	51.8	10.90	0.6	*		1			*		*	*		
	45, 50																
Quantum	55, 60	190	68.3	51.8	10.90	0.6	*		1			*		*	*		
	45, 50																
Quantum I/C	55, 60	190	68.3	51.8	11.00	0.6	*		1			*		*	*		
Intek OHV	55	170	68.3	45.7	14.30	0.65		*	1			*		*	*		
Intek Edge OHV	60	190	68.3	51.8	14.30	0.65		*	1			*		*	*		
Intek Pro OHV	65	190	68.3	51.8	15.20	0.77		*	1			*		*	*	*	
<b>RIDE-ON</b>																	
Power Built	10, 11, 12	465	87.3	77.70	30.00	1.42	*		1			*		*	*		
	10.5, 11.5,																
I/C	12.5	465	87.3	77.70	30.00	1.42	*		1			*		*	*		
Diamond I/C	13	465	87.3	77.70	30.00	1.42	*		1			*		*	*		opt.
I/C Quiet	12.5	465	87.3	77.70	30.00	1.42	*		1			*		*	*		opt.
I/C Quiet OHV	14.5	465	87.3	77.70	32.70	1.42		*	1			*		*	*		opt.
Diamond I/C OHV	15.5	465	87.3	77.70	32.70	1.42		*	1			*		*	*		opt.
I/C High Pref. OHV	16.5	502	90.7	77.70	34.80	1.42		*	1			*		*	*		opt.
Intek OHV	17	502	90.7	77.70	34.50	1.42		*	1			*		*	*		*
Intek OHV AVS	13.5	344	87.3	57.50	29.03	1.42		*	1			*		*	*		*
	15.5	465	87.3	77.70	34.70	1.42		*	1			*		*	*		*
	17.5	502	90.7	77.70	34.80	1.42		*	1			*		*	*		*
	18, 20,																
Intek V_Twin OHV	22	656	75.4	73.40	36.80	1.89		*	2			*		*	*		full
	25	725	79.3	73.40	36.70	1.89		*	2			*		*	*		full
ELS	15.5	465	87.3	77.70	34.70	1.42		*	1			*		*	*		full
	17.5	502	90.7	77.70	34.80	1.42		*	1			*		*	*		full
Vanguard V-Twin OHV	14, 16	480	68.0	66.00	32.40	1.70		*	2			*		*	*		full
	18, 20	570	72.0	70.00	33.30	1.70		*	2			*		*	*		full
	21, 23	627	75.5	70.00	35.00	1.70		*	2			*		*	*		full

	POWER LEVEL	DISPLACEMENT (CUBIC CM)	BORE (mm)	STROKE (mm)	WEIGHT (kg)	OIL CAPACITY (Liters)	VALVE		CYLINDER		AIR CLEANER			IGNITION	LUBRICATION		
							SIDE VALVE	OHV	ALUMINUM	CAST IRON SLEEVE	OILED FOAM	PAPER	DUAL-CLEAN	MAGNETRON	SPLASH TUBE	PRESSURE FILTRATION	PRESSURE LUBRICATION
<b>HORIZONTAL</b>																	
Power Built	3.5	148	65.1	44.4	9.20	0.60	*		1			*		*	*		
Power Built OHV	5.5, 6.5	206	68.3	55.8	15.31	0.60		*	1			*		*	*		
	8, 10	305	79.2	62.0	22.95	0.80		*	1			*		*	*		
Industrial Plus	3.5	148	65.1	44.4	13.50	0.60	*			1		*		*	*		
Intek I/C OHV	5.5, 6.5	206	68.3	55.8	15.31	0.60		*		1		*		*	*		
	8, 10	305	79.2	62.0	22.95	0.80		*		1		*		*	*		
I/C Apposed Twin	16	694	87.3	57.9	42.60	1.42	*			2		*		*	*		
	18	694	87.3	57.9	42.60	1.53	*			2		*		*	*		
Cast Iron	10	362	87.3	60.3	41.73	1.90	*			1		*		*	*		
	16	531	90.5	82.6	48.30	1.90	*			1		*		*	*		
Intek Pro OHV	5.5, 6.5	206	68.3	55.8	15.31	0.60		*		1		*		*	*		
	8, 10	305	79.2	62.0	23.40	0.80		*		1		*		*	*		
Intek Snow OHV	6.5, 7.5	206	68.3	55.8	15.40	0.60		*		1		*		*	*		
	9, 10	305	79.2	62.0	23.40	0.80		*		1		*		*	*		
	13	342	83.8	62.0	23.40	0.80		*		1		*		*	*		
Vanguard OHV	4	126	62.0	42.0	16.10	0.60		*		1		*		*	*		
	6	182	68.0	50.0	19.50	0.70		*		1		*		*	*		
	7.5	215	72.0	52.0	21.50	0.90		*		1		*		*	*		
	9	296	80.0	59.0	27.30	1.40		*		1		*		*	*		
	11, 13	391	89.0	63.0	33.20	1.50		*		1		*		*	*		
Vanguard V-Twin OHV	16	480	68.0	66.0	32.40	1.70		*		2		*		*	*	*	
	18	570	72.0	70.0	33.30	1.70		*		2		*		*	*	*	
	20, 22	627	75.5	70.0	35.00	1.70		*		2		*		*	*	*	
DM700D	18	697	68.0	64.0	82.00	2.99		*		3		*	*	*	*	*	
DM850D	23.6	850	68.0	78.0	84.00	2.99		*		3		*		*	*	*	
DM950D	26.5	952	72.0	78.0	84.00	2.99		*		3		*		*	*	*	
DM950D TURBO	31	952	72.0	78.0	89.00	2.99		*		3		*		*	*	*	
DM954D TURBO	34	952	72.0	78.0	89.00	2.99		*		3		*		*	*	*	
DM700G	24.5	697	68.0	64.0	70.00	2.99		*		3		*		*	*	*	
DM950G	31	952	72.0	78.0	72.00	2.99		*		3		*		*	*	*	
DM954G	34	952	72.0	78.0	72.00	2.99		*		3		*		*	*	*	